



SLD



Works deeper and consistently achieves a top quality finish



TOGETHER WE'RE EVEN STRONGER

The SLD is a deeper working version of the SL cultivator. It incorporates some of the principles of the well-proven and ever popular Solo, and bridges the gap between the two machines. Equipped with Pro-Lift hydraulic reset tines and a DD rear roller, the SLD leaves an excellent level finish, while also performing an effective loosening operation.

Designed using the latest computer-aided techniques, the SLD chassis is built to take the stresses and punishment of use with tractors up to 650hp in its stride – season after season, after season.

THE SLD RESTRUCTURES THE SUB-SOIL DOWN TO 300mm AND LEAVES A FINE, WEATHERPROOF SEEDBED



DRAWBAR OPTIONS

The SLD is equipped with a Cat 4 drawbar hitch (Cat 5 available as an option). A single hydraulic ram permits sideways movement and reduces stress levels. A rear drawbar complete with four hydraulic lines can also be specified, for pulling a single or double press in tandem with the cultivator.



DD 700 REAR ROLLER

The rear DD roller, with 700mm diameter shouldered press rings, consolidates the ground through to depth and leaves a ridged, weather-proof seedbed that is ready for drilling or can be left to weather over the winter. Proven one-piece scrapers are fitted as standard.



PRO-LIFT HYDRAULIC RESET TINES

Simba's Pro-Lift hydraulic reset legs run up to 150mm deeper than the discs and to a maximum depth of 300mm. A choice of wings can be fitted to suit soil type, conditions and trash levels.



EASY DISC ANGLE ADJUSTMENT

Fully adjustable disc angling enables you to vary how aggressively the soil is worked. Select an acute angle for maximum mixing of stubble in one pass and a shallower angle to chop down ploughing when required.



TWO GANGS OF PRO-ACTIVE DISCS


Two rows of 600mm Pro-Active discs, one ahead of the tines and one behind, chop and incorporate high volumes of surface trash. Spaced at 250mm, the discs give improved contour following and excellent stone protection.



300 - 650HP



4.6m - 6.0m



DOWN TO 300mm



TECHNICAL SPECIFICATIONS

Model	Width (m)	Weight (kg)	No. of Tines	No. of Discs	Tine Spacing (mm)	Power Req (hp)
SLD 460	4.6	9,880	7	36	665mm	300-650
SLD 600	6.0	11,500	9	48	665mm	400-650

STANDARD FEATURES

- Disc diameter 600mm
- Disc spacing (net) 125mm
- Fully adjustable disc angling
- Working depths of tines 0-150mm below disc depth
- Tine type – Pro-Lift hydraulic reset
- DD rear roller 700mm diameter, 230mm DD ring spacing
- Transport width 3.0m
- Hydraulic brakes
- Full European road lighting kit
- Flotation tyres – 700/50 – 22.5, 16 ply



HYDRAULIC RESET SUBSOILER TINES



PRO-ACTIVE DISC UNIT

OPTIONAL EXTRAS

- Rear drawbar complete with four hydraulic pipes
- Air brakes kit (in lieu of hydraulic)
- Factory fitted OSR Kit (8 outlets)
- Cat 5 shackle (in lieu of Cat 4)



SLD

Simba International Ltd, Woodbridge Road, Sleaford, Lincolnshire. NG34 7EW. England
 Tel: 01529 304654 | Email: sales@simba.co.uk | Fax: 01529 413468 | www.simba.co.uk

Global Headquarters

Great Plains Manufacturing, Inc. 1525 East North Street, Salina, Kansas 67401-5060 USA
 Tel: +1-785-823-3276 | Fax: +1-785-822-6722 | e-mail: gpi@greatplainsmfg.com | www.greatplainsmfg.com



TOGETHER WE'RE EVEN STRONGER