



# UNIPRESS



The combined cultivator and press for light to medium soils



TOGETHER WE'RE EVEN STRONGER

The Unipress from Simba is designed to carry out several operations in one pass on light to medium soils, saving you both time and money.

The machine features leading tines which cultivate and create a tilth ahead of the full width, fully-adjustable levelling board which further works the soil, aligning clods ahead of the in-line large diameter 700mm DD Rings. The rings crush the clods and leave a well cultivated, consolidated and weatherproof seedbed which is usually ready for drilling with no further cultivation.

# UNIPRESS SAVES YOU TIME AND MONEY WITH THREE OPERATIONS IN ONE PASS



120-260HP



4.6m - 8.2m



2760 - 4920 kg



### CRANKED TINE OPTION

A cranked leg with a 100mm sweep tine is available where shallower work is required



### BRAKED AXLE AND ROAD LIGHTING KIT

An axle brake kit and a full road lighting kit are fitted as standard.



### PRO-ACTIVE TINES

Simba's Pro-Active tines are mounted on a 150mm x 14mm sprung leaf which offers greater vibration and cultivation, while also protecting against stone damage by enabling the tines to trip out of the soil and re-set in work immediately.



### LEVELLING BOARD INTERMESHERS WITH DD ROLLER

The leaves of the levelling board intermesh with the DD roller. This patented arrangement effectively aligns the clods with the sharp edge of the ring ensuring they are crushed in one pass.



### ADJUSTABLE LEVELLING BOARD

The fully adjustable Simba levelling board can be hydraulically rotated to vary the pitch and depth of the board so as to ensure maximum effectiveness in varying soil types.




### 700mm DD REAR ROLLER

The rear in-line DD roller with 700mm diameter DD rings ensures an even weight balance in work irrespective of ground undulations, consolidates the soil through to depth and leaves a high quality, weatherproof finish.

### DD Effect

Clods are cut and fissures propagate through a result of the DD action



Broken or cracked clods are left in an ideal state for further weathering



# TECHNICAL SPECIFICATIONS

Model	Working Width (m)	No. of Pro-Active Tines	Weight (kg)	Power Req (hp)
<b>UNIPRESS</b>	4.6	15	2760	120-170
	5.5	17	3300	140-190
	6.6	21	3960	150-220
	7.2	23	4560	180-240
	8.2	27	4920	200-260

## STANDARD FEATURES

- Pro-Active sprung tines for improved protection and trash clearance
- Straight leg or cranked tine options
- Levelling board intermeshing with DD roller
- 700mm diameter DD roller, 230mm DD ring spacing
- Hydraulically braked axle
- Road lights
- All models fold to under 3m for transport



LEVELLING BOARDS



DD700

## OPTIONAL EXTRAS

- Rear drawbar complete with 4 pipes
- Cranked tine with sweep on Pro-Active tine
- Speed-Lube (fully automated or manual centralised)
- Extending drawbar



# UNIPRESS

Simba International Ltd, Woodbridge Road, Sleaford, Lincolnshire. NG34 7EW. England  
 Tel: 01529 304654 | Email: sales@simba.co.uk | Fax: 01529 413468 | www.simba.co.uk

### Global Headquarters

Great Plains Manufacturing, Inc. 1525 East North Street, Salina, Kansas 67401-5060 USA  
 Tel: +1-785-823-3276 | Fax: +1-785-822-6722 | e-mail: gpi@greatplainsmfg.com | www.greatplainsmfg.com



TOGETHER WE'RE EVEN STRONGER