



# X-PRESS



The flexible choice for high-speed shallow cultivations



TOGETHER WE'RE EVEN STRONGER

A compact disc harrow with an integrated press roll, the versatile X-Press combines high speed shallow cultivations with effective consolidation.

Available as a mounted machine in 2.5m, 3m, 3.5m and 4m widths and as a trailed unit in 4.6m, 5.5m, 6.6m 8m and 10m widths, the X-Press can be used in reduced cultivation systems, to incorporate stubble or to work down ploughing in more conventional regimes.

The versatility of the reliable, well-proven X-Press is further enhanced by the ability to vary the angle of the discs ensuring penetration in hard conditions and eliminating the need to carry large amounts of ballast weight.

# FOR REDUCED TILLAGE SYSTEMS, STUBBLE INCORPORATION OR TO WORK DOWN PLOUGHING – THE X-PRESS EXCELS



## DISC DEPTH ADJUSTMENT

Easy front and rear disc depth adjustment provides even more flexibility to suit different conditions and applications



## EASY DISC ANGLE ADJUSTMENT

Disc angling is fully adjustable between 0° and 25° enabling you to vary how aggressively the soil is worked and ensure good penetration. Select an acute angle for maximum mixing of stubble in one pass and a shallower angle to chop down ploughing when required.



## PRO-ACTIVE DISC UNITS

The Pro-Active disc units give improved protection against stone damage. The chrome vanadium steel mounts, with a trip height of 120mm, also offer improved contour following whilst maintaining a consistent depth at high forward speed.

5.5m Trailed X-Press



3.0m Mounted X-Press



## ST BAR OPTION ON MOUNTED X-PRESS

An ST Bar can be fitted ahead of the Mounted X-Press transforming the machine into a one-pass cultivator, which can restructure the soil, taking out compaction caused by harvest traffic, down to a depth of 25cm.



70 - 480HP



2.5 - 10.0m



1,525 - 14,000 kg



## DD REAR ROLLER

Trailed units are equipped with a 700mm diameter DD rear roller, whilst the smaller mounted machines benefit from a set of 550mm diameter DD Lites. The full width roller, with its familiar shouldered press rings, consolidates the ground through to depth, leaving a fine, corrugated finish that is weatherproof in dry or wet conditions.



## EXCELLENT TRASH CLEARANCE

The design of the X-Press, mounted and trailed models, results in a massive amount of clearance between both gangs of discs and the rear DD roller to ensure that it will operate in conditions with high volumes of trash.



## TWO ROWS OF DISCS

Mounted individually, the cultivation discs are 500mm in diameter. The disc spacing is 250mm on both front and rear gangs, giving a net disc spacing between gangs of 125mm. Their rotational speed is far greater than more conventional discs. Chopping and mixing is enhanced and a finer seedbed is achieved.



# TECHNICAL SPECIFICATIONS

## MOUNTED X-PRESS

Working Width (m)	Transport Width (m)	Weight (kg)	No. of Discs	Power Req (hp)
2.5	2.50	1,525	18	70-110
3.0	3.00	1,750	22	80-120
3.5	3.50	2,000	26	90-150
4.0	4.00	2,440	30	110-170
4.0	2.98	2,920	32	125-180

## TRAILED X-PRESS

Working Width (m)	Transport Width (m)	Weight (kg)	No. of Discs	Power Req (hp)
4.6	2.95	5,540	36	140-180
5.5	2.95	6,350	44	160-220
6.6	2.95	7,570	52	200-260
8.0	2.95	11,500	62	300-420
10.0	2.95	14,000	80	350-480

### OPTIONAL EXTRAS - MOUNTED X-PRESS

- OSR 6 Kit
- Trailing kit on 4.0m Folding Wing model
- Open Cage Roller in lieu of DD Roller
- Aqueel II Roller in lieu of DD Roller



The trailing kit for the Mounted X-Press available for the Folding Wing model allows a tractor from 125hp to pull the 4m machine.

### OPTIONAL EXTRAS - TRAILED X-PRESS

- OSR 8 Kit (not 8m & 10m)
- Rear Drawbar with hydraulic services (not 4m, 8m & 10m)
- Track eradicators (not 4m, 8m & 10m)
- Hydraulic brakes (4.6m – 6.6m models)
- Air brakes (4.6m – 6.6m models)
- Levelling board in front of rear roller (8m & 10m only)
- Aqueel II roller in lieu of DD Lite roller
- OSR Kit (6 outlets)



Optional Aqueel roller



Optional cage roller



# X-PRESS

Simba International Ltd, Woodbridge Road, Sleaford, Lincolnshire. NG34 7EW. England  
 Tel: 01529 304654 | Email: sales@simba.co.uk | Fax: 01529 413468 | www.simba.co.uk

#### Global Headquarters

Great Plains Manufacturing, Inc. 1525 East North Street, Salina, Kansas 67401-5060 USA  
 Tel: +1-785-823-3276 | Fax: +1-785-822-6722 | e-mail: gpi@greatplainsmfg.com | www.greatplainsmfg.com



TOGETHER WE'RE EVEN STRONGER